

Especificaciones



La foto es representativa



Eaton 5P1000

Eaton 5P UPS, Tower, 1000 VA, 770 W, 5-15P input, Outputs: (8) 5-15R, 120V, true sine wave, network card optional

General specifications

PRODUCT NAME	Eaton 5P UPS
CATALOG NUMBER	5P1000
UPC	743172042996
PRODUCT LENGTH/DEPTH	13.6 in
PRODUCT HEIGHT	9.1 in
PRODUCT WIDTH	5.9 in
PRODUCT WEIGHT	25.3 lb
COMPLIANCES	RoHS Compliant CE Marked
CERTIFICATIONS	IEC 62040-2 C1-C2 / EN 55024 / CISPR22 Class B / FCC part 15 Class B UL 1778 UL 497A cULus Listed



Powering Business Worldwide

Especificaciones del producto

SPECIAL FEATURES	ROO/RPO: Rear terminal block connector for remote on/off and power off
TOPOLOGY	Line-interactive
COLOR	Black/silver
VA RATING	1000 VA
WATTAGE	770 W
PACKAGE CONTENTS	• 5P UPS • User manual CD • Intelligent Power Software Suite CD • Quick start guide • USB cable • RS-232 serial cable
INPUT CONNECTION	5-15P
INPUT CORD LENGTH	6 ft
INPUT NOMINAL VOLTAGE	120V default (100/110/120/127V)
NOMINAL FREQUENCY	50-60 Hz
INPUT FREQUENCY RANGE	47-70 Hz (50 Hz system), 56.5-70 Hz (60 Hz system), 40-70 Hz in low-sensitivity mode
INPUT POWER FACTOR	0.77
RECEPTACLE	(8) 5-15R
OUTPUT WAVEFORM	Sine wave
VOLTAGE	120V
OUTPUT NOMINAL VOLTAGE	120V default (100/120/125V)
FEED TYPE	1
RUNTIME GRAPH	\$row.attributeValue.cdata
BATTERY MANAGEMENT	ABM technology (3-stage charging extends battery service life by 50% and provides advance warning for battery replacement)
BATTERY REPLACEMENT	User replaceable
BATTERY TYPE	Sealed, lead-acid
EXTENDED BATTERY CAPABILITY	None; See Eaton 5PX UPS for extended runtimes options
STANDARD FACTORY WARRANTY	• 3-YEAR FACTORY WARRANTY w/ REGISTRATION • -3 years

Recursos

	• -Parts, electronics, and batteries coverage • -Standard ground shipping • -Technical support
EXTENDED SERVICE PLANS	• ADVANCED DEPOT EXCHANGE • -5-YEAR DEPOT REPAIR: 5SW5Y-1400UC • -Expedited parts coverage for 5 years • -Parts, electronics and UPS batteries coverage • -Next business day shipping • -Technical support • 5-YEAR ON-SITE PLAN: WFLN75XX-2509UC • - On-site parts and labor coverage for years 5 • - Parts, electronics and UPS batteries coverage • - 24x7 on-site labor coverage, next-day response • - Next-day shipping • - Technical support
COMMUNICATION	RS-232 (RJ45) ports; USB port as standard (HID). 6-foot RS-232 and USB cables included
EXPANSION SLOTS	One slot; Gigabit Network Card (Network-M3) is optional
SOFTWARE COMPATIBILITY	Eaton Intelligent Power Manager
USER INTERFACE	LCD graphical display
ALTITUDE	Up to 10,000 ft (3000m) without de-rating
BTU RATING	Online: 106, Battery 500
NOISE LEVEL	<45 dB at 1 meter
RELATIVE HUMIDITY	0-90% non-condensing
TEMPERATURE RANGE	0° to 35°C (32° to 95°F)
EFFICIENCY AT MAX. LOAD	97%

INPUT VOLTAGE RANGE	89-151 Vac (adjustable to 70-153 Vac)
OUTPUT POWER FACTOR	0.77
OUTPUT VOLTAGE RANGE	102-132 Vac
QUANTITY	1

NOMBRE DE PROYECTO:
NÚMERO DE PROYECTO:
PREPARADO POR:
FECHA:



Eaton Corporation plc Eaton House
Carretera 30 Pembroke
Dublín 4, Irlanda
Eaton.com

© 2026 Eaton. Todos los derechos reservados.

Síganos en las redes sociales para que conozca la información sobre productos y soporte más reciente.

