

Especificaciones



Eaton 5P1500

Eaton 5P UPS, Tower, 1440 VA, 1100 W, 5-15P input, Outputs: (8) 5-15R, 120V, true sine wave, network card optional

General specifications

PRODUCT NAME	Eaton 5P UPS
CATALOG NUMBER	5P1500
UPC	743172043009
PRODUCT LENGTH/DEPTH	17.5 in
PRODUCT HEIGHT	9.1 in
PRODUCT WIDTH	5.9 in
PRODUCT WEIGHT	35.6 lb
COMPLIANCES	CE Marked RoHS Compliant
CERTIFICATIONS	cULus Listed UL 1778 UL 497A IEC 62040-2 C1-C2 / EN 55024 / CISPR22 Class B / FCC part 15 Class B



Powering Business Worldwide

Especificaciones del producto

SPECIAL FEATURES	ROO/RPO: Rear terminal block connector for remote on/off and power off
TOPOLOGY	Line-interactive
COLOR	Black/silver
VA RATING	1440 VA
WATTAGE	1100 W
PACKAGE CONTENTS	<ul style="list-style-type: none">• 5P UPS• User manual CD• Intelligent Power Software Suite CD• Quick start guide• USB cable• RS-232 serial cable
INPUT CONNECTION	5-15P
INPUT CORD LENGTH	6 ft
INPUT NOMINAL VOLTAGE	120V default (100/110/120/127V)
NOMINAL FREQUENCY	50-60 Hz
INPUT FREQUENCY RANGE	47-70 Hz (50 Hz system), 56.5-70 Hz (60 Hz system), 40-70 Hz in low-sensitivity mode
INPUT POWER FACTOR	0.77
RECEPTACLE	(8) 5-15R
OUTPUT WAVEFORM	Sine wave
VOLTAGE	120V
OUTPUT NOMINAL VOLTAGE	120V default (100/120/125V)
FEED TYPE	1
RUNTIME GRAPH	\$row.attributeValue.cdata
BATTERY MANAGEMENT	ABM technology (3-stage charging extends battery service life by 50% and provides advance warning for battery replacement)
BATTERY REPLACEMENT	User replaceable
BATTERY TYPE	Sealed, lead-acid
EXTENDED BATTERY CAPABILITY	None; See Eaton 5PX UPS for extended runtimes options
STANDARD FACTORY WARRANTY	<ul style="list-style-type: none">• 3-YEAR FACTORY WARRANTY w/ REGISTRATION• -3 years

Recursos

- -Parts, electronics, and batteries coverage
- -Standard ground shipping
- -Technical support

EXTENDED SERVICE PLANS

- ADVANCED DEPOT EXCHANGE
- -5-YEAR DEPOT REPAIR: 5SW5Y-1750UC
- -Expedited parts coverage for 5 years
- -Parts, electronics and UPS batteries coverage
- -Next business day shipping
- -Technical support
- 5-YEAR ON-SITE PLAN: WFLN75XX-2509UC
- - On-site parts and labor coverage for years 5
- - Parts, electronics and UPS batteries coverage
- - 24x7 on-site labor coverage, next-day response
- - Next-day shipping
- - Technical support

COMMUNICATION

RS-232 (RJ45) ports; USB port as standard (HID). 6-foot RS-232 and USB cables included

EXPANSION SLOTS

One slot; Gigabit Network Card (Network-M3) is optional

SOFTWARE COMPATIBILITY

Eaton Intelligent Power Manager

USER INTERFACE

LCD graphical display

ALTITUDE

Up to 10,000 ft (3000m) without de-rating

BTU RATING

Online: 113, Battery 714

NOISE LEVEL

<45 dB at 1 meter

RELATIVE HUMIDITY

0-90% non-condensing

TEMPERATURE RANGE

0° to 40°C (32° to 104°F)

EFFICIENCY AT MAX. LOAD

97%

INPUT VOLTAGE RANGE	89-151 Vac (adjustable to 70-153 Vac)
OUTPUT POWER FACTOR	0.76
OUTPUT VOLTAGE RANGE	102-132 Vac
QUANTITY	1

NOMBRE DE PROYECTO:

NÚMERO DE PROYECTO:

PREPARADO POR:

FECHA:



Eaton Corporation plc Eaton House
Carretera 30 Pembroke
Dublín 4, Irlanda
Eaton.com

Síguenos en las redes sociales para que conozca la información sobre productos y soporte más reciente.



© 2026 Eaton. Todos los derechos reservados.