

# Especificaciones

## Eaton 9PX6KG2

Eaton 9PX Gen 2 UPS, 6000 VA, 5400 W,  
Input: Hardwired or 10ft. L6-30P, Outputs:  
Hardwired, (2) L6-30R, (2) L6-20R, 3U  
Rack/tower, VRLA battery, Gigabit Network  
card included

### General specifications

<b>PRODUCT NAME</b>	Eaton 9PX UPS
<b>CATALOG NUMBER</b>	9PX6KG2
<b>UPC</b>	786689860066
<b>PRODUCT LENGTH/DEPTH</b>	26.93 in
<b>PRODUCT HEIGHT</b>	5.12 in
<b>PRODUCT WIDTH</b>	17.32 in
<b>PRODUCT WEIGHT</b>	98.33 lb
<b>COMPLIANCES</b>	CISPR22 Class A / FCC part 15 Class A FCC Part 15 CE Marked
<b>CERTIFICATIONS</b>	NOM cULus Listed IEC 62040-2:2006 Cat C2 ENERGY STAR certified ICC-ES AC156 OSHPD Seismic certified



Powering Business Worldwide

## Especificaciones del producto

<b>SPECIAL FEATURES</b>	Gigabit Network Card (NETWORK-M3) included
<b>TOPOLOGY</b>	Online/Double-conversion
<b>RACK SIZE</b>	3U
<b>COLOR</b>	Black/silver
<b>VA RATING</b>	6000 VA
<b>WATTAGE</b>	5400 W
<b>RACK MOUNTING KIT</b>	Yes
<b>PACKAGE CONTENTS</b>	<ul style="list-style-type: none"><li>• 6000VA 5400W 9PX G2 Online Double-Conversion UPS</li><li>• NETWORK-M3 Gigabit network card</li><li>• USB cable</li><li>• RS-232 cable</li><li>• Cable gland for hardwire connection</li><li>• Rack-mounting hardware</li><li>• Tower support stands</li><li>• Quick Start Guide</li></ul>
<b>SURGE PROTECTION</b>	Yes
<b>INTERNAL BYPASS</b>	Yes
<b>INPUT CONNECTION</b>	L6-30P and hardwire input supported
<b>INPUT CORD LENGTH</b>	10 ft
<b>INPUT NOMINAL VOLTAGE</b>	208V default (200/208/220/230/240V)
<b>INPUT FREQUENCY RANGE</b>	60 Hz: 50–70 Hz, 50 Hz: 40–60 Hz
<b>INPUT POWER FACTOR</b>	>0.99 typical
<b>RECEPTACLE</b>	(2) L6-20R, (2) L6-30R, Hardwired
<b>NUMBER OF OUTPUTS L6-20R</b>	2
<b>NUMBER OF OUTPUTS L6-30R</b>	2
<b>OUTPUT WAVEFORM</b>	True sine wave
<b>VOLTAGE</b>	208 V
<b>OUTPUT NOMINAL VOLTAGE</b>	208V default (200/208/220/230/240V)
<b>RUNTIME GRAPH</b>	\$row.attributeValue.cdata
<b>BATTERY MANAGEMENT</b>	ABM+ technology uses battery replacement

## Recursos

DECLARATIONS OF CONFORMITY

[Eaton 9PX Gen2 Declaration of Conformity](#)

	analytics to predict when you should replace UPS batteries based on real-life usage and conditions.
<b>BATTERY REPLACEMENT</b>	Hot-swappable internal batteries and extended battery modules (EBMs). Replacement battery part # EBP-1805 (qty 1 per UPS)
<b>BATTERY TYPE</b>	Sealed, lead-acid
<b>EXTENDED BATTERY CAPABILITY</b>	Add up to 12 EBMs, part # 9PXEBM180RTG2
<b>STANDARD FACTORY WARRANTY</b>	<ul style="list-style-type: none"> <li>• 3-YEAR FACTORY WARRANTY</li> <li>• - 3 years</li> <li>• - Parts, electronics and batteries coverage</li> <li>• - Standard ground shipping</li> <li>• - Technical support</li> </ul>
<b>EXTENDED SERVICE PLANS</b>	<ul style="list-style-type: none"> <li>• ADVANCED DEPOT EXCHANGE</li> <li>• - 5-year depot repair: 9SW5Y-6000UC</li> <li>• - Expedited parts coverage for 5 years</li> <li>• - Parts, electronics and UPS batteries coverage</li> <li>• - Next business day shipping</li> <li>• - Technical support</li> <li>•</li> <li>• 5 YEAR ON-SITE PLAN: WFLN75XX-6009UC</li> <li>• - On-site parts and labor coverage for 5 years</li> <li>• - Parts, electronics and UPS batteries coverage</li> <li>• - 24x7 on-site labor coverage, next day response</li> <li>• - Next-day shipping</li> <li>• - Technical support</li> </ul>
<b>RUNTIME AT HALF LOAD</b>	8.3 min
<b>EXPANSION SLOTS</b>	(1) Mini-Slot (MS) expansion port with Gigabit Network Card

	(NETWORK-M3) included
<b>ETHERNET INTERFACE</b>	Yes
<b>INCLUDES NETWORK CARD</b>	Yes
<b>SOFTWARE COMPATIBILITY</b>	Brightlayer Data Centers suite
<b>USER INTERFACE</b>	Graphical display, 5-button programmable menu, LED indicator
<b>ALTITUDE</b>	3000 m
<b>BTU RATING</b>	Online: 767 BTU/hr, Battery: 1155 BTU/hr, High Efficiency: 205 BTU/hr
<b>NOISE LEVEL</b>	<43 dB at 1 meter
<b>RELATIVE HUMIDITY</b>	0-95% non-condensing
<b>TEMPERATURE RANGE</b>	0° to 40°C (32° to 104°F)
<b>PROTOCOL</b>	SNMP

**PRODUCT HIGHLIGHTS**

- Keeps equipment running during outages to allow time for file saves and safe shutdown
- Best-in-class efficiency results in reduced energy costs and greenhouse gas emissions
- Included NETWORK-M3 Gigabit network card enables full remote access and control
- Exclusive ABM+ technology and analytics help you pinpoint when to replace batteries
- Optional extended battery modules allow expanded runtime to keep equipment powered

<b>EFFICIENCY AT MAX. LOAD</b>	96%
<b>MAX NUMBER OF BATTERY PACKS</b>	12
<b>OUTPUT FREQUENCY</b>	50/60 Hz
<b>OUTPUT POWER FACTOR</b>	0.9 (240V L6-30P), 1.0 (hardwired input)
<b>OUTPUT VOLTAGE RANGE</b>	±1% steady-state
<b>RUNTIME AT FULL LOAD</b>	3 min. (5400W)
<b>OUTPUT CAPACITY DETAILS</b>	240V: 5400 watts (L6-30P input); 230V: 5300 watts (L6-30P input); 220V: 5100 watts (L6-30P input); 208V: 4800 watts (L6-30P input);

200V: 4600 watts (L6-30P input); 200V - 240V: 6000 watts (hardwired UPS input)

**NOMBRE DE PROYECTO:**

**NÚMERO DE PROYECTO:**

**PREPARADO POR:**

**FECHA:**



**Eaton Corporation plc** Eaton House  
Carretera 30 Pembroke  
Dublín 4, Irlanda  
Eaton.com

Síguenos en las redes sociales para que conozca la información sobre productos y soporte más reciente.



© 2026 Eaton. Todos los derechos reservados.