

Especificaciones



Eaton 9SX1000

Eaton 9SX online, extended runtime UPS, 1000 VA, 900 W, 5-15P input, Outputs: (6) 5-15R, 9.9"Hx6.3"Wx15.1"D, 30.9 lb., network card optional

General specifications

PRODUCT NAME	Eaton 9SX UPS
CATALOG NUMBER	9SX1000
UPC	743172091239
PRODUCT LENGTH/DEPTH	15.1 in
PRODUCT HEIGHT	9.9 in
PRODUCT WIDTH	6.3 in
PRODUCT WEIGHT	30.9 lb
COMPLIANCES	FCC Compliant CE Marked ENERGY STAR certified
CERTIFICATIONS	cULus Listed ICC-ES AC156 OSHPD Seismic certified



Powering Business Worldwide

Batería

RUNTIME GRAPH [View runtime graph](#)

BATTERY MANAGEMENT ABM technology (3-stage charging extends battery service life by 50% and provides advance warning for battery replacement)

BATTERY REPLACEMENT Hot-swappable internal batteries and extended battery modules (EBMs)

EXTENDED BATTERY CAPABILITY Yes

Entrada eléctrica

INPUT CONNECTION 5-15P

INPUT CORD LENGTH 8 ft

INPUT NOMINAL VOLTAGE 120 Default (100/110/120/125V)

INPUT FREQUENCY RANGE 60 Hz: 50–70 Hz, 50 Hz: 40–60 Hz

INPUT POWER FACTOR >.99

Salida eléctrica

RECEPTACLE (6) 5-15R

TOPOLOGY Online/Double-conversion

WATTAGE 900 W

VA RATING 1000 VA

OUTPUT WAVEFORM True sine wave

VOLTAGE 120V

OUTPUT POWER FACTOR 0.9

OUTPUT NOMINAL VOLTAGE 120V default (100/110/120/125V)

OUTPUT FREQUENCY 50/60 Hz

FEED TYPE 1

Comunicaciones

- COMMUNICATION**
- (1) MiniSlot
 - (1) USB port
 - (1) Serial RS-232 port
 - (1) RPO/ROO/Signal input terminal
 - (1) mini-terminal block for output relay

- EXPANSION SLOTS**
- (1) Mini-Slot (MS) expansion port. Optional connectivity cards may be ordered separately.
 - - Gigabit Web/SNMP card part number: NETWORK-M3
 - - Modbus card part number: INDGW-M2
 - - Relay card part number: RELAY-MS

USER INTERFACE 5-button graphical user interface

POTENTIAL FREE SWITCH CONTACT Yes

Clasificación ambiental

ALTITUDE	3000 m
BTU RATING	Online : 421 BTU/hr, Battery : 505 BTU/hr, High efficiency : 208 BTU/hr
NOISE LEVEL	51 dB at 1m
RELATIVE HUMIDITY	0-96% non-condensing
TEMPERATURE RANGE	0° to 40°C (32° to 104°F)

Garantía y soporte

STANDARD FACTORY WARRANTY

- 3-YEAR FACTORY WARRANTY
- - 3 years
- - Parts, electronics and batteries coverage
- - Standard ground shipping
- - Technical support

EXTENDED SERVICE PLANS

- ADVANCED DEPOT EXCHANGE
- -5-year depot repair: 9SW5Y-1000UC
- -Expedited parts coverage for 5 years
- -Parts, electronics and UPS batteries coverage
- -Next business day shipping
- -Technical support
-
- 5-YEAR ON-SITE PLAN: WFLN75XX-2509UC
- - On-site parts and labor coverage for years 5
- - Parts, electronics and UPS batteries coverage
- - 24x7 on-site labor coverage, next-day response
- - Next-day shipping
- - Technical support

Especificaciones adicionales

CONSTRUCTION TYPE	Free standing model
EFFICIENCY AT MAX. LOAD	90.81
PACKAGE CONTENTS	<ul style="list-style-type: none">• 9SX 1000 VA UPS• Quick start guide• RS-232 serial cable• USB cable
INTERNAL BYPASS	Yes

Recursos

NOMBRE DE PROYECTO:

NÚMERO DE PROYECTO:

PREPARADO POR:

FECHA:



Eaton Corporation plc Eaton House
Carretera 30 Pembroke
Dublín 4, Irlanda
Eaton.com

Síguenos en las redes sociales para que conozca la información sobre productos y soporte más reciente.

© 2026 Eaton. Todos los derechos reservados.

