

# Especificaciones

## Eaton 9SX2000

Eaton 9SX online, extended runtime UPS, 2000 VA, 1800 W, 5-20P input, Outputs: (6) 5-20R, (1) L5-20R, 13.6"Hx8.4"Wx16.2"D, 77.2 lb., network card optional

### General specifications

<b>PRODUCT NAME</b>	Eaton 9SX UPS
<b>CATALOG NUMBER</b>	9SX2000
<b>UPC</b>	743172091253
<b>PRODUCT LENGTH/DEPTH</b>	16.2 in
<b>PRODUCT HEIGHT</b>	13.6 in
<b>PRODUCT WIDTH</b>	8.4 in
<b>PRODUCT WEIGHT</b>	77.2 lb
<b>COMPLIANCES</b>	FCC Compliant CE Marked
<b>CERTIFICATIONS</b>	cULus Listed ICC-ES AC156 OSHPD Seismic certified



Powering Business Worldwide

## Batería

<b>RUNTIME GRAPH</b>	\$row.attributeValue.cdata
<b>BATTERY MANAGEMENT</b>	ABM technology (3-stage charging extends battery service life by 50% and provides advance warning for battery replacement)
<b>BATTERY REPLACEMENT</b>	Hot-swappable internal batteries and extended battery modules (EBMs)
<b>EXTENDED BATTERY CAPABILITY</b>	Yes

## Entrada eléctrica

<b>INPUT CONNECTION</b>	5-20P
<b>INPUT CORD LENGTH</b>	8 ft
<b>INPUT NOMINAL VOLTAGE</b>	120 Default (100/110/120/125V)
<b>INPUT FREQUENCY RANGE</b>	60 Hz: 50–70 Hz, 50 Hz: 40–60 Hz
<b>INPUT POWER FACTOR</b>	>.99

## Salida eléctrica

<b>RECEPTACLE</b>	(6) 5-20R, (1) L5-20R
<b>TOPOLOGY</b>	Online/Double-conversion
<b>WATTAGE</b>	1800 W
<b>VA RATING</b>	2000 VA
<b>OUTPUT WAVEFORM</b>	True sine wave
<b>VOLTAGE</b>	120V
<b>OUTPUT POWER FACTOR</b>	0.9
<b>OUTPUT NOMINAL VOLTAGE</b>	120V default (100/110/120/125V)
<b>OUTPUT FREQUENCY</b>	50/60 Hz
<b>FEED TYPE</b>	1

## Comunicaciones

<b>COMMUNICATION</b>	<ul style="list-style-type: none"><li>• (1) MiniSlot</li><li>• (1) USB port</li><li>• (1) Serial RS-232 port</li><li>• (1) RPO/ROO/Signal input terminal</li><li>• (1) mini-terminal block for output relay</li></ul>
----------------------	---

<b>EXPANSION SLOTS</b>	<ul style="list-style-type: none"><li>• (1) Mini-Slot (MS) expansion port. Optional connectivity cards may be ordered separately.</li><li>• - Gigabit Web/SNMP card part number: NETWORK-M3</li><li>• - Modbus card part number: INDGW-M2</li><li>• - Relay card part number: RELAY-MS</li></ul>
------------------------	--

<b>USER INTERFACE</b>	5-button graphical user interface
-----------------------	-----------------------------------

<b>POTENTIAL FREE SWITCH CONTACT</b>	Yes
--------------------------------------	-----

## Clasificación ambiental

<b>ALTITUDE</b>	3000 m
<b>BTU RATING</b>	Online : 813 BTU/hr, Battery : 1103 BTU/hr, High efficiency : 342 BTU/hr
<b>NOISE LEVEL</b>	<53 dB at 1 meter
<b>RELATIVE HUMIDITY</b>	0-96% non-condensing
<b>TEMPERATURE RANGE</b>	0° to 40°C (32° to 104°F)

## Garantía y soporte

### STANDARD FACTORY WARRANTY

- 3-YEAR FACTORY WARRANTY
- - 3 years
- - Parts, electronics and batteries coverage
- - Standard ground shipping
- - Technical support

### EXTENDED SERVICE PLANS

- ADVANCED DEPOT EXCHANGE
- - 5-year depot repair: 9SW5Y-2200UC
- - Expedited parts coverage for 5 years
- - Parts, electronics and UPS batteries coverage
- - Next business day shipping
- - Technical support
- 
- 5-YEAR ON-SITE PLAN: WFLN75XX-6009UC
- - On-site parts and labor coverage for years 5
- - Parts, electronics and UPS batteries coverage
- - 24x7 on-site labor coverage, next-day response
- - Next-day shipping
- - Technical support

## Especificaciones adicionales

<b>CONSTRUCTION TYPE</b>	Free standing model
<b>EFFICIENCY AT MAX. LOAD</b>	89.4%
<b>PACKAGE CONTENTS</b>	<ul style="list-style-type: none"><li>• 9SX 2000 VA UPS</li><li>• Quick start guide</li><li>• RS-232 serial cable</li><li>• USB cable</li></ul>
<b>INTERNAL BYPASS</b>	Yes

## Recursos

---

**NOMBRE DE PROYECTO:**

**NÚMERO DE PROYECTO:**

**PREPARADO POR:**

**FECHA:**

---



**Eaton Corporation plc** Eaton House  
Carretera 30 Pembroke  
Dublín 4, Irlanda  
Eaton.com

Síguenos en las redes sociales para que conozca la información sobre productos y soporte más reciente.

© 2026 Eaton. Todos los derechos reservados.

