

Especificaciones



Eaton 9SX3000

Eaton 9SX online, extended runtime UPS, 3000 VA, 2700 W, 120V, L5-30P input, Outputs: (4) 5-20R, (1) L5-30R, 13.6"Hx8.4"Wx16.2"D, 77.2 lb., network card optional

General specifications

PRODUCT NAME	Eaton 9SX UPS
CATALOG NUMBER	9SX3000
UPC	743172091260
PRODUCT LENGTH/DEPTH	16.2 in
PRODUCT HEIGHT	13.6 in
PRODUCT WIDTH	8.4 in
PRODUCT WEIGHT	77.2 lb
COMPLIANCES	FCC Compliant CE Marked
CERTIFICATIONS	cULus Listed ICC-ES AC156 OSHPD Seismic certified



Powering Business Worldwide

Batería

RUNTIME GRAPH	\$row.attributeValue.cdata
BATTERY MANAGEMENT	ABM technology (3-stage charging extends battery service life by 50% and provides advance warning for battery replacement)
BATTERY REPLACEMENT	Hot-swappable internal batteries and extended battery modules (EBMs)
EXTENDED BATTERY CAPABILITY	Yes

Entrada eléctrica

INPUT CONNECTION	L5-30P
INPUT CORD LENGTH	8 ft
INPUT NOMINAL VOLTAGE	120 Default (100/110/120/125V)
INPUT FREQUENCY RANGE	60 Hz: 50–70 Hz, 50 Hz: 40–60 Hz
INPUT POWER FACTOR	>.99

Salida eléctrica

RECEPTACLE	(4) 5-20R, (1) L5-30R
TOPOLOGY	Online/Double-conversion
WATTAGE	2700 W
VA RATING	3000 VA
OUTPUT WAVEFORM	True sine wave
VOLTAGE	120V
OUTPUT POWER FACTOR	0.9
OUTPUT NOMINAL VOLTAGE	120V default (100/110/120/125V)
OUTPUT FREQUENCY	50/60 Hz
FEED TYPE	1

Comunicaciones

COMMUNICATION	<ul style="list-style-type: none">• (1) MiniSlot• (1) USB port• (1) Serial RS-232 port• (1) RPO/ROO/Signal input terminal• (1) mini-terminal block for output relay
----------------------	-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

EXPANSION SLOTS	<ul style="list-style-type: none">• (1) Mini-Slot (MS) expansion port. Optional connectivity cards may be ordered separately.• - Gigabit Web/SNMP card part number: NETWORK-M3• - Modbus card part number: INDGW-M2• - Relay card part number: RELAY-MS
------------------------	--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

USER INTERFACE	5-button graphical user interface
-----------------------	-----------------------------------

POTENTIAL FREE SWITCH CONTACT	Yes
--------------------------------------	-----

Clasificación ambiental

ALTITUDE	3000 m
BTU RATING	Online : 1020 BTU/hr, Battery : 1340 BTU/hr, High efficiency : 350 BTU/hr
NOISE LEVEL	<53 dB at 1 meter
RELATIVE HUMIDITY	0-96% non-condensing
TEMPERATURE RANGE	0° to 40°C (32° to 104°F)

Garantía y soporte

STANDARD FACTORY WARRANTY

- 3-YEAR FACTORY WARRANTY
- - 3 years
- - Parts, electronics and batteries coverage
- - Standard ground shipping
- - Technical support

EXTENDED SERVICE PLANS

- ADVANCED DEPOT EXCHANGE
- - 5-year depot repair: 9SW5Y-3000UC
- - Expedited parts coverage for 5 years
- - Parts, electronics and UPS batteries coverage
- - Next business day shipping
- - Technical support
- 5-YEAR ON-SITE PLAN: WFLN75XX-6009UC
- - On-site parts and labor coverage for years 5
- - Parts, electronics and UPS batteries coverage
- - 24x7 on-site labor coverage, next-day response
- - Next-day shipping
- - Technical support

Especificaciones adicionales

CONSTRUCTION TYPE	Free standing model
EFFICIENCY AT MAX. LOAD	90.9
PACKAGE CONTENTS	<ul style="list-style-type: none">• 9SX 3000 VA UPS• Quick start guide• RS-232 serial cable• USB cable
INTERNAL BYPASS	Yes

Recursos

NOMBRE DE PROYECTO:

NÚMERO DE PROYECTO:

PREPARADO POR:

FECHA:



Eaton Corporation plc Eaton House
Carretera 30 Pembroke
Dublín 4, Irlanda
Eaton.com

Síguenos en las redes sociales para que conozca la información sobre productos y soporte más reciente.

© 2026 Eaton. Todos los derechos reservados.

