

# Especificaciones



## Eaton 9SX3000GL

Eaton 9SX online, extended runtime UPS, 3000 VA, 2700 W, L6-20P input, Outputs: (1) L6-30R, (2) L6-20R, (2) 6-20R, 13.6"Hx8.4"Wx16.2"D, 77.2 lb., network card optional

### General specifications

<b>PRODUCT NAME</b>	Eaton 9SX UPS
<b>CATALOG NUMBER</b>	9SX3000GL
<b>UPC</b>	743172091321
<b>PRODUCT LENGTH/DEPTH</b>	16.2 in
<b>PRODUCT HEIGHT</b>	13.6 in
<b>PRODUCT WIDTH</b>	8.4 in
<b>PRODUCT WEIGHT</b>	77.2 lb
<b>COMPLIANCES</b>	FCC Compliant CE Marked
<b>CERTIFICATIONS</b>	cULus Listed ICC-ES AC156 OSHPD Seismic certified



Powering Business Worldwide

## Batería

<b>RUNTIME GRAPH</b>	\$row.attributeValue.cdata
<b>BATTERY MANAGEMENT</b>	ABM technology (3-stage charging extends battery service life by 50% and provides advance warning for battery replacement)
<b>BATTERY REPLACEMENT</b>	Hot-swappable internal batteries and extended battery modules (EBMs)
<b>EXTENDED BATTERY CAPABILITY</b>	Yes

## Entrada eléctrica

<b>INPUT CONNECTION</b>	L6-20P
<b>INPUT CORD LENGTH</b>	8 ft
<b>INPUT NOMINAL VOLTAGE</b>	208V default (200/208/220/230/240V)
<b>INPUT FREQUENCY RANGE</b>	60 Hz: 50–70 Hz, 50 Hz: 40–60 Hz
<b>INPUT POWER FACTOR</b>	>.99

## Salida eléctrica

<b>RECEPTACLE</b>	(1) L6-30R, (2) L6-20R, (2) 6-20R
<b>TOPOLOGY</b>	Online/Double-conversion
<b>WATTAGE</b>	2700 W
<b>VA RATING</b>	3000 VA
<b>OUTPUT WAVEFORM</b>	True sine wave
<b>VOLTAGE</b>	208 V
<b>OUTPUT POWER FACTOR</b>	0.9
<b>OUTPUT NOMINAL VOLTAGE</b>	208V default (200/208/220/230/240/250V)
<b>OUTPUT FREQUENCY</b>	50/60 Hz
<b>FEED TYPE</b>	1

## Comunicaciones

- (1) MiniSlot
- (1) USB port
- (1) Serial RS-232 port
- (1) RPO/ROO/Signal input terminal
- (1) mini-terminal block for output relay

- (1) Mini-Slot (MS) expansion port. Optional connectivity cards may be ordered separately.
- - Gigabit Web/SNMP card part number: NETWORK-M3
- - Modbus card part number: INDGW-M2
- - Relay card part number: RELAY-MS

**USER INTERFACE** 5-button graphical user interface

**POTENTIAL FREE SWITCH CONTACT** Yes

## Clasificación ambiental

<b>ALTITUDE</b>	3000 m
<b>BTU RATING</b>	Online : 861 BTU/hr, Battery : 1408 BTU/hr, High efficiency : 304 BTU/hr
<b>NOISE LEVEL</b>	<53 dB at 1 meter
<b>RELATIVE HUMIDITY</b>	0-96% non-condensing
<b>TEMPERATURE RANGE</b>	0° to 40°C (32° to 104°F)

## Especificaciones adicionales

<b>CONSTRUCTION TYPE</b>	Free standing model
--------------------------	---------------------

<b>EFFICIENCY AT MAX. LOAD</b>	92.2%
--------------------------------	-------

### PACKAGE CONTENTS

- 9SX 3000 VA UPS
- Quick start guide
- 8-foot C19 to L6-20P input connector
- RS-232 serial cable
- USB cable

<b>INTERNAL BYPASS</b>	Yes
------------------------	-----

## Garantía y soporte

### **STANDARD FACTORY WARRANTY**

- 3-YEAR FACTORY WARRANTY
- - 3 years
- - Parts, electronics and batteries coverage
- - Standard ground shipping
- - Technical support

### **EXTENDED SERVICE PLANS**

- ADVANCED DEPOT EXCHANGE
- - 5-year depot repair: 9SW5Y-3000UC
- - Expedited parts coverage for 5 years
- - Parts, electronics and UPS batteries coverage
- - Next business day shipping
- - Technical support
- 
- 5-YEAR ON-SITE PLAN: WFLN75XX-6009UC
- - On-site parts and labor coverage for years 5
- - Parts, electronics and UPS batteries coverage
- - 24x7 on-site labor coverage, next-day response
- - Next-day shipping
- - Technical support

## Recursos

---

**NOMBRE DE PROYECTO:**

**NÚMERO DE PROYECTO:**

**PREPARADO POR:**

**FECHA:**

---



**Eaton Corporation plc** Eaton House  
Carretera 30 Pembroke  
Dublín 4, Irlanda  
Eaton.com

Síguenos en las redes sociales para que conozca la información sobre productos y soporte más reciente.

© 2026 Eaton. Todos los derechos reservados.

